## FABRITEC TECHNICAL SLANT

# Fabritec 5970 RESTORE

Products/Procedures

**Fabritec 5970 RESTORE** eliminates smoke and many other odors such as perspiration, vomit and pet odors by chemically reacting with the offending odors. Although this product is especially formulated for the restoration expert, all cleaners will benefit from its use. RESTORE can eliminate ozone treatment in the restoration process for all but the most severely smoke damaged articles. RESTORE can be used in both perchloroethylene and hydrocarbon drycleaning systems, as well as in laundry and wetcleaning systems.

#### **USE INSTRUCTIONS:**

## Drycleaning:

Add 1 to 2 oz. RESTORE for each 10 pounds of articles in the load. RESTORE can be added to the wheel of the drycleaning unit via a dosing unit or injection devise, by hand to the button trap, or poured between the basket and washer shell prior to loading the articles. For maximum results RESTORE should be batched or milled in the solvent for up to 5 minutes prior to the filter run.

## Laundry & Wetcleaning:

RESTORE can be used in the laundry in conjunction with 5911/5931 TITANIUM Detergent at a rate of 1/2 to 1 ounce for every 1 ounce of TITANIUM detergent.

In a wetcleaning process, RESTORE can be used in conjunction with 5925 COTTON CLEAN or 5914 SILKY CLEAN at a rate of 2-4 oz. per 50 lb. washer.

Note: Safety Data Sheet (SDS) available by request. Call 1-800-543-0406.